FIRE COM

UHW505

Radio Transmit Under-Helmet DECT7 Wireless Headset





This rugged headset features DECT7 wireless technology for improved sound quality in the apparatus and on the fire scene. Extended range and coverage let you communicate clearly with crew members up to 1,000 feet from the apparatus.



FEATURES



DECT7® WIRELESS COMMUNICATIONS

Full-duplex crew communication. Integrates with the 5000D Series Digital Intercom and WB505R wireless base station for a complete apparatus communication system.



RUGGED AND TESTED

Built to withstand environmental extremes, the UHW505 is ready for rain, water, mud or snow.



RADIO TRANSMIT

Direct-wire interface to any portable radio with a Firecom PR Adapter (sold separately).



AUTO-LEVELING MICROPHONE

Be heard clearly as you move from low- to high-noise areas.



HEARING PROTECTION

Passive noise reduction eliminates unsafe noise.



LISTEN-THROUGH SITUATIONAL AWARENESS

Hear your surroundings and have face-to-face conversations without removing your hearing protection.



AUTOMATIC LOUD NOISE SUPPRESSION

The UHW505 automatically limits high impulse noises such as gunshots from being transmitted to the user in Stereo Listen-Through mode.



UNMATCHED AUDIO CLARITY

High-definition, wideband audio provides greater clarity and understanding of mission-critical communications.



NOISE CANCELLING MICROPHONE

Be understood even in the loudest environments.



AUTO-ON

The UHW505 automatically powers on when disconnected from the charging cable.





UHW505 Radio Transmit Under-Helmet DECT7 Wireless Headset



FEATURES

ROBUST DESIGN

Flexible microphone boom

2-stage microphone cover eliminates wind noise

Enhanced durability and comfort; designed to fit any head size

Microphones protected by a layer of waterproof material for outdoor use

STATE-OF-THE-ART HEARING PROTECTION

Sound suppressor reduces loud noise while enhancing other sounds Stereo Listen-Through microphones allow face-to-face conversation and situational awareness

24dB passive noise reduction rating (NRR)

LONG-LASTING POWER SOURCE

24-hour rechargeable lithium-ion battery

User-replaceable battery

Energy-saver sleep mode: one year of shelf life without losing charge

Simple on/off operation

Power-on battery capacity LED indicator

Audible and visual 2-stage low battery warning

110/220V DC battery charger included

Heavy-duty 12V DC charging cable included

TOTAL CONFIGURABILITY

Features are custom programmable to user specifications

Programmable microphone gain

Voice prompts for easy feature navigation and feedback

CUSTOMIZABLE

Silicone ruggedizers for position or function ID. Available in 14 colors**:



**Custom colors available: min_order 50 pairs_Call

SPECIFICATIONS

DECT7® WIRELESS TECHNOLOGY

Dynamic channel allocation

DECT Standard Cipher with 40-bit initialization vector Frequency Bandwidth: 1920 MHz to 1930 MHz

PHYSICAL

Weight: 16 oz. (without ruggedizers)

Color: Black

Noise Reduction Rating: 24dB NRR

Side Pressure: 2.2 lbs.

POWER

3.7V rechargeable lithium ion battery

More than 24 hours of battery life at 77°F (25°C)

Charge time: 4 hours

AC Charge Source: supplied 12V, 500mA wall charger

DC Charge Source: 5V to 16V, 1.5A minimum, cable supplied

Over voltage, under voltage, over current and over temperature protection

ENVIRONMENTAL

Operating temperature -22°F (-30°C) to +140°F (+60°C) Storage temperature -4°F (-20°C) to +122°F (+50°C) Charging temperature 32°F (0°C) to +113°F (+45°C)

MIL

Humidity per MIL-STD 810F and 810G Temperature Shock per MIL-STD 810F and 810G Chemical Exposure per MIL-STD 810

SAE

Salt Spray per J1455, Sec. 4.3 Vibration per J1455, Sec. 4.9 Conducted Immunity per J1113-11 Electrostatic Discharge per J1113-13 Radiated Emissions per CISPR 25 Radiated Immunity per ISO 11452-2

ISO

Conducted Transients per 7637-2 Quality Management System ISO 9001:2008







